

# Safety Data Sheet

according to OSHA Hazard Communication  
29 CFR Part 1910.1200



## Section 1. Identification

**Identification Number:** 27-3001103  
**Product Name:** SWC NATUREONE 100% ACRY EN PEC  
**Product Use/Class:** Exterior Stain

### SUPPLIER:

Structures Wood Care  
24530 Hazelwood Dr. PO Box 599  
Nisswa, MN 46568  
Information: 866-963-4680

CHEMTEL NORTH AMERICA 1-800-255-3924  
WORLDWIDE INTL. 1-813-248-0585  
24 HR. EMERGENCY HOTLINE

**Safety Data Sheet Coordinator:** J. Michael Jacobs (614) 253-8511

## Section 2. Hazard(s) Identification

**EMERGENCY OVERVIEW:** COMBUSTIBLE liquid and vapor. Harmful if inhaled. Harmful if swallowed. May cause target organ or system damage (e.g., lung, nervous system, blood disorders, liver, kidney, immune system, cardiovascular system, thyroid, testicular, ovarian, etc.). Vapors irritating to eyes and respiratory tract. High vapor concentrations may cause drowsiness. Vapors may cause flash fire or explosion.

### GHS Classification

Flam. Liq. 4, Repr. 2, Skin Sens. 1

### Symbol(s) of Product



### Signal Word

warning

### GHS HAZARD STATEMENTS

Flammable liquid, category 4	H227	Combustible liquid
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Reproductive Toxicity, category 2	H361	Suspected of damaging fertility or the unborn child. Classified Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/fetal lethality, post natal functional deficiencies.

### PRECAUTIONARY STATEMENTS: DISPOSAL

P501 Dispose of contents/container according to applicable local, national, and international regulations.

### PRECAUTIONARY STATEMENTS: PREVENTION

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.

**PRECAUTIONARY STATEMENTS: RESPONSE**

P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see supplemental first aid instruction on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: use recommended media to extinguish.

**PRECAUTIONARY STATEMENTS: STORAGE**

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

### Section 3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
DIPROPYLENE GLYCOL METHYL ETHER	34590-94-8	4-5	No Information	H227
DIBUTYL PHTHALATE (HAP)	84-74-2	2-3	GHS07-GHS08	H332-361
BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL)SEBACATE	41556-26-7	0-1	GHS07	H227-317

### Section 4. First-Aid Measures



**FIRST AID - INHALATION:** Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention.

**FIRST AID - SKIN CONTACT:** Wash with soap and water. Get medical attention if irritation develops or persists.

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water. Get medical attention if irritation persists.

**FIRST AID - INGESTION:** If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

**MOST IMPORTANT SYMPTOMS:** Eye irritation signs/symptoms may include a burning sensation, redness, swelling, and/or blurred vision. Skin irritation signs/symptoms may include a burning sensation, redness, swelling, and/or blisters. If inhaled signs/symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. Onset of respiratory symptoms may be delayed for several hours following exposure. Inhalation of high vapor concentrations may cause central nervous system depression resulting in dizziness, light-headedness, headache, nausea, and loss of coordination. Continued inhalation may result in unconsciousness and death.

**INDICATION OF IMMEDIATE MEDICAL ATTENTION IF NECESSARY:** If symptoms persist call a poison control center or a doctor/physician.

### Section 5. Fire-Fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Vapors may form explosive mixture with air. Vapors can travel to a source of ignition and flash back. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty containers should be completely drained, properly sealed, and promptly recycled or properly disposed of. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and may be ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Eliminate or shut off ALL ignition sources prior to usage. Combustible liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint.

**SPECIAL FIREFIGHTING PROCEDURES:** Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire. Move containers from fire area if it can be done without risk.

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

## Section 6. Accidental Release Measures

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES:** ELIMINATE all ignition sources (no smoking, flares, sparks, flames, or motor vehicles of any kind in the immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do so without risk.

**ENVIRONMENTAL PRECAUTIONS:** Prevent entry into waterways, sewers, basements, and other confined spaces.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Contain and absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways.

## Section 7. Handling and Storage



**HANDLING:** Wash thoroughly after handling. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment.

**STORAGE:** Keep away from heat, sparks and flame. Keep container closed when not in use. Keep from freezing.

## Section 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
DIPROPYLENE GLYCOL METHYL ETHER	100 PPM	150 PPM	100 PPM	150 PPM
DIBUTYL PHTHALATE (HAP)	5 mg/m <sup>3</sup>	N.E.	5 mg/m <sup>3</sup>	N.E.
BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL)SEBACATE	N.E.	N.E.	N.E.	N.E.

**Legend:** MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

### Protective Measures



**ENGINEERING CONTROLS:** Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.



**RESPIRATORY PROTECTION:** A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.



**SKIN PROTECTION:** Use chemical resistant splash goggles and face shield (ANSI Z87.1 or approved equivalent). The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Rubber, nitrile or neoprene to prevent skin contact.



**EYE PROTECTION:** Wear safety glasses with side shields (or goggles) and a face shield.



**OTHER PROTECTIVE EQUIPMENT:** Wear chemical resistant shoes. Rubber or plastic apron should be worn.



**HYGIENIC PRACTICES:** Wash hands before eating. Remove contaminated clothing and wash before reuse. Follow all SDS/label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

## Section 9. Physical and Chemical Properties

<b>Appearance:</b>	Brown Liquid	<b>Physical State:</b>	Liquid
<b>Odor:</b>	Typical Latex	<b>Odor Threshold:</b>	N.D.
<b>Specific Gravity:</b>	1.049	<b>pH:</b>	8.7-9.2
<b>Freeze Point, °C:</b>	0	<b>Viscosity:</b>	400-450 cps
<b>Solubility in Water:</b>	Soluble	<b>Partition Coefficient, n-octanol/ water:</b>	N.D.
<b>Decomposition Temp., °C:</b>	N.D.	<b>Explosive Limits, vol%:</b>	0.5 - 14.0
<b>Boiling Range, °C:</b>	100 - 343	<b>Flash Point, °C:</b>	76.6
<b>Evaporation Rate:</b>	Slower than Diethyl Ether	<b>Vapor Pressure:</b>	N.D.
<b>Vapor Density:</b>	N.D.		

(See "Other information" Section for abbreviation legend)

## Section 10. Stability and Reactivity

**REACTIVITY:** No Information

**STABILITY:** This product is stable under normal storage conditions.

**POSSIBILITY OF HAZARDOUS REACTIONS:** None under normal processing conditions.

**CONDITIONS TO AVOID:** Do not freeze. Strong oxidizing or reducing agents.

**INCOMPATIBILITY:** Strong acids and strong bases.

**HAZARDOUS DECOMPOSITION PRODUCTS:** May produce fumes when heated to decomposition, as in welding or fire. Fumes may contain: Carbon Monoxide, Carbon Dioxide and various other hydrocarbons.

## Section 11. Toxicological Information



### Practical Experiences

**EFFECT OF OVEREXPOSURE - INHALATION:** Harmful if inhaled. Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor or skin exposure. Prolonged inhalation may be harmful. Proper respiratory equipment **MUST** be worn when sanding or abrading surfaces painted with this product. Sanding or abrading the dried paint film increases the risk of exposure. When incorporated in the liquid paint, pigments or extenders pose minimal risk of exposure.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Causes skin irritation. Allergic reactions are possible. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

**EFFECT OF OVEREXPOSURE - INGESTION:** This material may be harmful or fatal if swallowed. Irritating to mouth, throat and stomach.

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

### STOT - SINGLE EXPOSURE

No Additional Information

### STOT - REPEATED EXPOSURE

No Additional Information

**Carcinogenicity:** The information below indicates whether each agency has listed any ingredient as a carcinogen if present at levels greater than or equal to 0.1 %.

<u>CAS-No.</u>	<u>Name</u>	<u>NTP</u>	<u>OSHA</u>	<u>IARC</u>
----------------	-------------	------------	-------------	-------------

34590-94-8	DIPROPYLENE GLYCOL METHYL ETHER	Not listed by NTP	Not listed by OSHA	Not listed by IARC
84-74-2	DIBUTYL PHTHALATE (HAP)	Not listed by NTP	Not listed by OSHA	Not listed by IARC
41556-26-7	BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL)SEBACATE	Not listed by NTP	Not listed by OSHA	Not listed by IARC

National Toxicological Program (NTP), Occupational Safety & Health Association (OSHA), International Agency for Research on Cancer (IARC) Group 1: Carcinogenic to Humans, Group 2A: Probably Carcinogenic to Humans, Group 2B: Possibly Carcinogenic to Humans, Group 3: Not Classifiable as to its Carcinogenicity to Humans

#### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name according to EEC	Oral LD50 (mg/kg)	Dermal LD50 (mg/kg)	Vapor LC50 (mg/L)
34590-94-8	DIPROPYLENE GLYCOL METHYL ETHER	>5000 (rat)	>2000 (rabbit)	No Information
84-74-2	DIBUTYL PHTHALATE (HAP)	8000 (rat)	>20000 (rabbit)	>15.86 (4 h, rat)
41556-26-7	BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL)SEBACATE	3200 (rat)	No Information	No Information

## Section 12. Ecological Information

**ECOLOGICAL INFORMATION:** No Information

**MOBILITY IN SOIL:** No Information

**OTHER ADVERSE EFFECTS:** No Information

## Section 13. Disposal Considerations



Product

**DISPOSAL METHOD:** Dispose of in accordance with all local, state, and federal regulations. Approved incinerator or approved hazardous waste facility.

## Section 14. Transport Information

**SPECIAL TRANSPORT PRECAUTIONS:** No Information

**ENVIRONMENTAL HAZARDS:** No Information

**TRANSPORT IN BULK:** See DOT Information below.

**DOT Proper Shipping Name:** NOT REGULATED  
**DOT UN/NA Number:** N.A.  
**DOT Hazard Class:** N.A.  
**DOT Technical Name:** N.A.  
**Exception:** N.A.

**Packing Group:** N.A.  
**Hazard SubClass:** N.A.  
**Resp. Guide Page:** N.A.

## Section 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
DIBUTYL PHTHALATE (HAP)	84-74-2
3-IODO-2-PROPYNILBUTYL CARBAMATE	55406-53-6
ETHYLENE GLYCOL (HAP)	107-21-1
AMMONIUM HYDROXIDE	1336-21-6
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2

#### TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

### U.S. State Regulations:

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%. For hazardous components see Section 3.

<u>Chemical Name</u>	<u>CAS-No.</u>
H2O	7732-18-5
ACRYLIC EMULSION	PROPRIETARY

#### CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
CARBON BLACK	1333-86-4
CRYSTALLINE SILICA	14808-60-7

#### CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	<u>CAS-No.</u>
DIBUTYL PHTHALATE (HAP)	84-74-2

### International Regulations: As follows -

#### CANADIAN REGULATORY INFORMATION:

This SDS has been prepared in compliance with Hazardous Product Regulations (HPR).

Canadian DSL: No Information

**Section 16. Other Information, Including Date of Preparation of the Last Revision**

**Revision Date:** 1/23/2019 **Supersedes Date:** 1/23/2019

**Datasheet produced by:** Regulatory Department

**HMIS Ratings:**

**Health:** 1 **Flammability:** 1 **Reactivity:** 0 **Personal Protection:** B

**Volatile Organic Compounds, lb/gal:** 1.11

**Volatile Organic Compounds Applied, lb/gal** 0.45

**Volatile Organic Compounds, gr/ltr:** 133

**Volatile Organic Compounds Applied, gm/ltr** 54

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information, STOT - Specific Target Organ Toxicity, MIR - Maximum Incremental Reactivity

The information on this safety data sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product, or where instructions and recommendations are not followed. The user assumes all risks incident to the use of the product and must communicate to employees and customers all warnings that relate to the potential exposure to this product. It is the responsibility of the user to comply with all Federal, State, and Local laws, regulations, and ordinances, and to assure that all workplace and disposal practices are in compliance with such. ALL WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.